MOBILE VERTICAL LIFT



Performance

Platform Height	5.94 m
Working Height	7.94 m
Drive Height	Max. Platform Height
Stowed Height	198 cm
Platform Entry Height	46 cm
Platform Size (W x L)	
Extension Platform	120 x 66 cm
Parcel Tray Platform	66 x 66 cm
Stock Picking Tray Size	71 x 64 cm
Overall Vehicle Length	
Extension Platform Retracted	150 cm
Parcel Tray Platform	165 cm
Overall Vehicle Width	
Extension Platform	82 cm
Parcel Tray Platform	82 cm
Gross Vehicle Weight	4.055
Extension Platform	1,055 kg
Parcel Tray Platform	1,055kg
Platform Capacity	100 1.
Extension Platform	160 kg
Parcel Tray Platform	115 kg 45 kg
Stock Picking Tray Drive Maximum Speed	45 KY
Platform Lowered	5.6 km/h
Platform Elevated	1 km/h
Turning Radius	Zero
Gradeability	20%
1	
Underclearance	5 cm

Standard Specifications

Power Source

Batteries Battery Charger Drive System

4 x 6V Deep Cycle AGM 25 Amp; 5-Hour Charge 4 Brush Direct Electric (planetary gear)

Tyres

Rear Drive & Steer Wheels Front Caster Wheels Tyre Material

32 x 10 cm 20 x 6 cm Non-Marking





Standard Features

- Heavy Duty Planetary
- Gear Drive Motors
- Low Maintenance Anodized
- Aluminum Mast • Safety Interlocked Controls
- Pistol-Grip Platform Control
- Single Joystick Drive and Steer Control—Solid State, Microprocessor Controlled
- Variable Speed Elevation Controls
- Automatic Pothole Protection System
- 1-1/2 Degree Tilt Alarm and Control
- Key Lock Main Power Switch

Accessories & Options

- Programmable 4-Digit Security Lock
- Fluorescent Light Tube Caddy

- · Automatic Power-Off Battery Saver Control
- Battery Discharge Indicators— Platform and Base
- Transportation Tie Downs
- Built-In Fork Truck Pockets
- Hourmeter
- All Motion Alarm
- Flashing Amber Beacon
- Lifting Eye for a Crane Hook
- Horn
- AS/ NZS 1418.10 Compliant
- - Tool Tray (20 x 45 x 12.5 cm)
 - AC Outlet to Platform



The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/ or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.

0800 222 111 021 500 486

sales@elevatedaccess.co.nz www.elevatedaccess.co.nz