

Model		0808E
<b>Dimensions</b>		
Max Working Height		10.1m (33'2")/8m (26'3")
A Max Platform Height		8.1m (26'7")/6m (19'8")
B Max Horizontal Extension		0.9m (3')
C Length-Stowed		2.46m (8')
D Width-Stowed		0.83m (2'9")
Height-stowed	Rail Folded	1.96m (6'5")
	E Rail Unfolded	2.36m (7'9")
F Wheelbase		1.88m (6'2")
Ground Clearance (Pothole Guard Stowed)		0.1m (4")
Ground Clearance (Pothole Guard Deployed)		25mm (0.98")
Platform Dimensions (L×W×H)		2.30m×0.8m×1.1m (7'67"×2'8"×3'7")
<b>Performance</b>		
Platform Allowable Occupants (Indoors/Outdoors)		2 persons/1 person
Platform Capacity		250kg (551lbs)
Drive Speed-Stowed		4km/h (2.5mph)
Drive Speed-Raised		0.8km/h (0.5mph)
Elevation Time (Unloaded)		30s~35s
Descent Time (Unloaded)		34s~39s
Gradeability		25%
Turning Radius (Inside/Outside)		0/2.1m
Tilt Rating (Front to Back/Side to Side)		3°/1.5°
Tire Spec/Type		380×125mm (15×5 in)/solid
<b>Power</b>		
Batteries		6V×4/225Ah
Power Source		24V DC
Drive Mode		Motor, front-wheel
Charger Input		100~240V AC
Charger Output		30A
Hydraulic System Capacity		14L(3.1gal)
<b>Weight</b>		
Weight (Indoor)		2,265kg (4,994lbs)
Standards Compliance		CE and AS1418

