

# **STAR 6 CRAWLER**















#### **GO EVERYWHERE**

- > High-precision driving & smoothness
- > Intermediate supporting wheels in crawler track system
- > Ability to go through uneven grounds and water puddles
- > Dedicated forklift pockets

## **GREAT AGILITY IN CONFINED WORKING AREA**

- > Compact machine: only 0.76 m width
- > Low turning radius
- > + 0.4 m platform extension
- > Platform with dedicated anti-slip step
- > Ergonomic & intuitive platform control box with battery level indicator

### **OPTIMAL TOTAL COST OF OWNERSHIP**

- > 3-stage-cylinder mast: no chain & no cable
- > Direct electric drive brushless AC motors
- > Easy access to components (hoods and dedicated hand pump)
- > Onboard diagnostic: Haulotte Activ'Screen





# **STAR 6 CRAWLER**


#### **VERTICAL MASTS**

#### TECHNICAL DATA

SIA	R 6	CRA	WL	ΕR
	E .	0 m		

	STAR O CRAWLER		
Working height	5.8 m		
Platform height	3.8 m		
Horizontal outreach	0.4 m extension		
Lift capacity - inside	200 kg (2 pers.)		
Lift capacity - outside	200 kg (1 pers.)		
Platform size	0.74 m x 1.0 m		
Platform size with extension	0.74 m x 1.44 m		
A Length	1.44 m		
<b>B</b> Width	0.76 m		
C Height - stowed	1.72 m		
■ Ground clearance	6 cm		
Drive speed proportional	0.8 - 2.2 km/h		
Turning radius - outside	1.25 m		
Tilt alarm	1.5° / 3°		
Gradeability	25 %		
Max driveable platf. height	0.7 m		
Rubber tracks - non marking	180 x 72 x 43		
Power source	2 x 12 V - 115 Ah (C5)		
Hydraulic system capacity	5 l		
Weight	1 175 kg		

# 0 o B



## **STANDARD** EQUIPMENT

- > Motion movement only in stowed position
- > 24 V electric drive brushless AC motors
- > 20 A battery charger
- > 2x12 V 115 Ah maintenance-free batteries
- > Battery level indicator
- > Haulotte Activ'Screen
- > Fork lifting pockets
- > Hoisting and lifting eyes
- > Door entry gate with lock
- > 2 drive speed
- > 2 steering and driving non marking rubber tracks
- > Hourmeter
- > Horn
- > Travel alarm
- > Emergency stop at cage and ground level
- > Lowering system
- > Handing pump for platform elevation
- > Control stations at cage and ground level
- > Mobile upper control box
- > 2 towing hooks
- > Platform extension deck + 0.4 m

#### **OPTIONS** AND ACCESSORIES

- > Lockable battery circuit breaker
- > Upper control box protection plastic cover
- > Joystick protection
- > Deadman pedal
- > Flashing light
- > Hydraulic oil for cold countries
- > Biodegradable oil

